

# CT Cart – Small



the leader in lightweight durability

## SPECIFICATIONS

### Applications:

The CT Cart – Small is designed to hold up to 20 round tables stacked on edge. A handle is provided at the swivel caster end of the cart allowing the user to steer the cart. The middle support bar is provided to separate the tables into two sections holding 10 tables in each section up on edge.

### QUICK SPECS

Width	Height	Depth
26 1/2"	39"	67"


### Primary Structure:

Part	Material Size
Main Frame	bent and punched 14 gauge (.083) steel sheet metal
Handle Sockets	1 1/4" x 11 gauge (.120 wall) round tubing
Front Handle	1" x 14 gauge (.083 wall) round tubing
Middle and End Supports	1" x 14 gauge (.083 wall) round tubing

### Casters:

The wheels shall be not less than 1 1/4" wide x 5" diameter, non-marring, flat tread, thermoplastic elastomer, with 3/8" ball or roller bearings.

Wheels shall be mounted on two swivel caster rigs and two fixed caster rigs. They shall have a load capacity of not less than 325 pounds each.



PART NUMBER EXAMPLE: CRTCTS30-36BLK2

[www.mitylite.com](http://www.mitylite.com) 1.800.327.1692 • 1.801.224.0589 • fax 1.801.224.6191